

## Brochure for Truffle E series

### SD-W AN Broadband Bonding with 3G/4G/LTE/5G failover



The Truffle-E series Software Defined WAN Orchestration and Broadband Bonding Appliance, enables cost-effective and self-healing Internet access for businesses, enterprise branch offices and other multi-tenant buildings. Aggregation and intelligent WAN orchestration of multiple Internet access lines boosts Internet performance and reliability. The Truffle-E aggregates and intelligently orchestrates up to eight (or optionally as many as sixteen) Internet lines to increase performance and up-time of applications and services that run over the Internet. Several DIA, DSL, cable, MPLS, metro-ethernet or fiber services from different ISPs can be aggregated to provide increased bandwidth. The Truffle E provides higher access capacity at a cost much lower than a single Internet access service and is ideal to boost the performance and reliability of real-time and non-real-time applications running over IP networks.

## Features

### Downlink/Uplink Bonding in Peered Mode

Truffle bonds Internet access lines for all types of traffic (including encrypted traffic such as VPN) for aggregated downlink and uplink capacity when peered over the Internet with another Truffle with VLL server license located at the headquarter office or data center. For single office setups optional Broadband Bonding Service subscription enables downlink/uplink bonding.

### Elastic Static IP

A static IP in the cloud is provided as part of the optional Broadband Bonding Service and is mapped onto the Truffle. This means that static IP is available for services and inbound network access even during WAN outages, as long as at least one of the WAN links is up.

### Aggregated Downlink Capacity in Standalone Mode

When not peered with another Truffle device, all HTTP downlink sessions can be configured to use the aggregated bandwidth of the combined Internet access links, even in the case of a single HTTP session. For non-HTTP downlink sessions and all uplink sessions, Truffle provides session-based intelligent load balancing across the access links if not peered with another Truffle.

### Self-healing WAN & Application Armor

In peered mode, in case of Internet access line failures, the Truffle keeps the ongoing sessions alive by making real-time per-packet routing decisions, even for the sessions in progress, without loss of data integrity. Additionally automatic failover protects against failures of one or more WAN link outages.

### Software-Defined WAN Orchestration

Truffle's Software Defined Networking architecture enables quick and easy implementation of sophisticated WAN orchestration algorithms that are application specific. Truffle provides real-time traffic & bandwidth management features based on traffic type and various network metrics, including latency, jitter, packet-loss and many other custom parameters.

### Strong AES Encryption

Truffle bonding tunnels have built-in security option with AES 256 encryption.

### Virtual Interfaces with WAN & Traffic Management

Truffle supports virtual interfaces that have load-balancing and failover logic layered on top of the real physical WAN interfaces. Specific type of traffic can then be selectively filtered onto the virtual interface to take advantage of the load-balancing and failover capabilities of the virtual interface.

### Traffic Shaping, Monitoring & Alerts

Traffic can be monitored via performance graphs over seconds/minutes/hours/days/months. Various realtime and non-realtime traffic types can be filtered and shaped. SNMP or non-SNMP alerts provide in depth network visibility and intelligence.

### Transparent Zero-touch Installation

The existing Local Area Network does not require any changes. No coordination, new equipment or software is needed from the Internet Service Provider(s). A remotely accessible browser-based interface provides quick and easy management and system monitoring.

### Advanced QoS Algorithms & VoIP Armor

All traffic routed through the Truffle is intelligently managed to prioritize real-time traffic. Additionally a unique set of proprietary algorithms are implemented to improve real-time traffic metrics such as optimizing end-user experience (i.e. MOS score) of VoIP applications.

### Dynamic DNS Load Balancing

Truffle can be configured to provide Dynamic DNS load-balancing for inbound requests for internally hosted servers such as web-server, ftp-server, mail-server etc.

### Cellular, 3G, 4G, LTE, 5G WAN Connections

can be added as WAN access links for additional reliability.

### Transparent Installation

Pass-through installation is quick and hassle-free and requires zero changes to the existing legacy firewall and zero changes to the existing LAN network.

### Built-in Firewall & Router

Truffle can be configured either in pass-through to function inline with the existing legacy firewalls/routers or, if preferred, can be installed as the primary firewall/router.

## Specifications

### Truffle Hardware Specifications

**Mechanical dimensions:** 438(W) x 292.1(D) x 44(H) mm, 17.25"(W) x 11.5"(D) x 1.73"(H)

**Weight:** 10.4lbs.

**Input power requirement:** 80 plus 250W full-range ATX

**USB ports:** 2 (for cellular data)

**LAN ports(GbE, auto-sensed):** 2 GbE copper RJ45 Ethernet connector. One WAN port to LAN port fail-to-wire in case of power outage.

**WAN ports(GbE, auto-sensed):** 8 GbE copper WAN ports (model E). Add-on module option for additional: 8 GbE copper (model EC) or 8 GbE SFP ports (model EF).

**Certifications:** FCC, CE, RoHS-2, UL

**Operating Temperature:** 32 – 104 F, 0 – 40 Celsius

**Operating Humidity Range:** 20-90% RH

**Storage Temperature Range:** -4 – 158 F, -20 – 70 Celsius

### Truffle Software Specifications

**Max throughput:** 1Gbps (load balancing), 940 Mbps (standalone), 800Mbps (peered).

**Max number of concurrent IP sessions:** 1,000,000

**Device management:** Cloud based, SNMP, Remote Syslog, Email alerts.

**DHCP and DNS servers:** DNS relay, Parallel DNS optimization, DHCP server.

**DDNS:** Support for dynamic DNS for multiple interfaces

**WAN Configuration:** Static IP, PPPoE, DHCP or passthrough. Failover-only or aggregate modes for cellular and other WAN ports. Interface binding.

**Routing:** NAT and IP forwarding, QoS and inbound/outbound VOIP quality management

## Truffle Add-on Options

**Model E:** 2 GbE copper Ethernet LAN, 8 GbE Ethernet WAN ports, VLL client license, fail-to-wire

**Model EC:** 2 GbE copper Ethernet LAN, 16 GbE Ethernet WAN ports, VLL client license, fail-to-wire

**Model EF:** 2 GbE copper Ethernet LAN, 8 GbE Ethernet + 8 GbE SFP Ethernet WAN ports, VLL client license, fail-to-wire

**VLL Server license add-on:** Available for all models.

Authorized Distributor :



### HQ Office (KL)

**SecureOne Distribution Sdn Bhd** (828358 - X)

No. 7, Jalan 109E, Desa Business Park, Taman Desa, Jalan Kelang Lama, 58100 Kuala Lumpur, Malaysia.

Tel : +6 (03) 7984 6086 Fax : +6 (03) 7984 6032

Email : sales@secureone.com.my

### Northern Office

**SecureOne Distribution (Northern) Sdn Bhd** (977172 - H)

1A-2-02 @ One Precint (1160) Lengkok Mayang Pasir, 11950 Bayan Baru, Penang, Malaysia.

Tel : +6 (04) 619 2692 Fax : +6 (04) 619 2699

Email : northern@secureone.com.my